

JF-ADVR-K7408

8ch Fribrid 4MP/5MP 8HDD ADVR



Features

- ◆ Support 8ch 5MP Unreal-time Encoding
- ◆ Support XVI/AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS,MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

Dimensions



JF-ADVR-K7408

8ch Fribrid 4MP/5MP 8HDD ADVR

Specification

| 8HDD | | |
|-------------------|--|---------------------------|
| Model | JF-ADVR-K7408 | |
| Video | | |
| Encode | 8CH*5MP@18fps | |
| Playback | 4CH*5MP@18fps | |
| Multi-Mode | Analog | 8CH*5M |
| | Hybrid | 4CH*5M(Analog)+4CH*5M(IP) |
| | IP | 32*1080P/16CH*3M/8CH*5M |
| Video Compression | H.264/H.264+ | |
| Audio | | |
| Compression | G.711A | |
| Interface | | |
| Video Input | 8*BNC | |
| Video Output | 1*VGA,1*HDMI | |
| Audio I/O | 8/1 | |
| Alarm I/O | 16/4 | |
| Ethernet | 1*10/100M/1000Mbps Ethernet port, RJ45 port | |
| PTZ Control | 1*RS485, 1*RS232,Support for multiple PTZ protocol | |
| USB | 2*USB2.0 | |
| Max HDD | 8×8TB | |
| General | | |
| Temperature | 0 °C - + 55 °C | |
| Humidity | 10% -90% RH | |
| Power | ATX | |
| Consumption | <15W(Without HDD) | |
| Dimension | 443mm(L)*427.5mm(W)*92mm(H) | |