

JF-ADVR-F7116-V2/F7132

16ch/32ch Fribrid 720P 4HDD ADVR



Features

- ◆ Support 16ch/32ch 1080N Unreal-time Encoding
- ◆ Support AHD/TVI/CVI/CVBS/IP Self-adaptive
- ◆ HDMI/VGA Simultaneous Video Output
- ◆ Support DHCP,FTP,DNS,DDNS,NTP,UPNP,EMAIL,3G,WIFI
- ◆ Support ONVIF Protocol
- ◆ Support WEB,VMS, MYEYE Platform
- ◆ Support Mobile Phone Monitoring(IOS ,Android)
- ◆ Cloud Services,P2P,Alarm Information Push To Phone
- ◆ Support Multi-Language

Dimensions



JF-ADVR-F7116-V2/F7132

16ch/32ch Fribrid 720P 4HDD ADVR

Specification

4HDD		
Model	JF-ADVR-F7116-V2	JF-ADVR-F7132
Video		
Encode	16CH*1080N@12fps	32CH*1080N@12fps
Playback	16CH*1080N@12fps	8CH*1080N@12fps
Multi-Mode	Analog	16CH*1080N
	Hybrid	8CH*1080N(Analog)+8CH*960P(IP)
	IP	8CH*1080P+8CH*960P/16CH*960P/4CH*3M/4*5M
Video Compression	H.264	
Audio		
Audio Compression	G.711A	
Interface		
Video Input	16*BNC	32*BNC
Video Output	1*VGA,1*HDMI	
Audio I/O	16/1	
Alarm I/O	16/4	
Ethernet	1*10/100M/1000Mbps Ethernet port, RJ45 port	
PTZ Control	1*RS485, 1*RS232,Support for multiple PTZ protocol	
USB	3*USB2.0	
Max HDD	4*8TB	
General		
Temperature	0 °C - + 55 °C	
Humidity	10%-90%RH	
Power	12V/6A	
Consumption	<15W(Without HDD)	
Dimension	440mm(L)* 400.5mm(W)* 60mm(H)	

JF TECH Co.,Ltd.
Headquarters(Hangzhou):
Building 9, Yinhu Innovation Center, Hangzhou, China
Business Center(Shenzhen):
A 7th Floor, Block Sakata 5 Avenue and Chong Hing Times Tower Shenzhen
All Rights Reserved • Specifications subject to change without notice.

Website:<http://www.jftech.com>
Tel:+86-0571-23271188
Tel:+86-0755-32898088